



## PRESTONETT® Interior / Exterior Flexible Crack Repair Filler

### GENERAL INFORMATION

#### DESCRIPTION

- Ready Mixed Flexible Crack Repair Filler

#### INTENDED USE

- Interior/exterior
- Repairs to reoccurring cracks due to structural movement

### PRODUCT ADVANTAGES

- ✓ Highly flexible & excellent surface adhesion
- ✓ Fibreglass reinforced for moving cracks
- ✓ Waterproof
- ✓ No fibre tape or fabric required
- ✓ White



# 1

## PRESTONETT®



N° 1.270



1

PRESTONETT®

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue: July 2013

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information cannot replace an appropriate description regarding the type and condition of the substrate. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that an updated edition of this sheet has not been issued.



## PRESTONETT® Interior / Exterior Flexible Crack Repair Filler

### TECHNICAL DATA

◉ PRESENTATION	Ready Mixed Filler
◉ COMPONENTS	Based on acrylic copolymers
◉ DENSITY	1.2 +/- 0.1
◉ pH	8 +/- 0.5
◉ COLOUR	White
◉ OPEN TIME AT 20°C	Unlimited
◉ WAITING TIME BEFORE OVERCOATING	2 – 24 hours depending on substrates, temperature and humidity conditions.
◉ CLASSIFICATION	AFNOR NFT 36 005 famille IV classe 4b: Waterborne exterior paint filler
◉ HEALTH AND SAFETY	Safety data sheet available on request or from <a href="http://www.quickfds.com">www.quickfds.com</a>
◉ PACKAGING	200 ml tube
◉ STORAGE	12 months in original sealed packaging, protected from frost, heat and moisture

### USE

◉ DILUTION	Ready mixed
◉ APPLICATION	Clean out crack, apply a bead down the length of the crack and then smooth with a spatula extending past the edge of the crack and ensure no air pockets are left. Allow to set for 6-8 hours before applying a second coat if required.
◉ IMPORTANT	This product is not sandable, smooth over with a wet spatula before completely dry to achieve a smooth surface.
• <i>Equipment</i>	Trowel or blade
• <i>Conditions</i>	Do not apply at temperatures of below +5°C or above +30°C, or at relative humidity of above 65% HR (hygrometry rate)
• <i>Equipment cleaning</i>	With water before completely dry
◉ APPLICATION THICKNESS	3 mm
◉ SUBSTRATES	Fine-grain concrete, concrete, cellular concrete, gypsum board, cement, concrete block, brick, plaster, ceramic tiles, old paint substrates. Substrates must be hard, cohesive, clean, sound and dry according to the local standards.
◉ OVERCOAT	Fibre Glass Cloth, Traditional Paints and Wall coverings
◉ TIPS	Can be over coated in a couple hours when repairing hair line cracks. Cracks (> 3mm) must first be filled with a suitable Prestonett Filler leaving a lip (< 3mm)