



▶▶ PRESTONETT® Interior Quick Dry filler

GENERAL INFORMATION

DESCRIPTION

- Quick-drying filler in powder

INTENDED USE

- Interior
- For filling holes and cracks of up to 40 mm
- Particularly suitable for renovation work
- Allows rapid overcoating

PRODUCTS ADVANTAGES

- ✓ Can be applied on damp substrates
- ✓ Does not shrink or crack
- ✓ Sandable after 90 minutes
- ✓ Can be overcoated after just 3 hours
- ✓ Brilliant White
- ✓ Excellent adhesion to many substrates



1

PRESTONETT®





1

PRESTONETT®

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue: October 2011

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information cannot replace an appropriate description regarding the type and condition of the substrate. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that an updated edition of this sheet has not been issued.



PRESTONETT® Interior Quick Dry filler

TECHNICAL DATA

○ PRESENTATION	Powder for mixing with water
○ COMPONENTS	Synthetic resin and hydraulic binders Selected inorganic fibres and fillers
○ pH	On mixing : 11 ± 1 After drying : 9 ± 1
○ COLOUR	White
○ OPEN TIME AT 20°C	Approximately 30 minutes
○ WAITING TIME BEFORE OVERCOATING	Approximately 3 hours at 20°C
○ CLASSIFICATION	NF T 36-005 - Family III, Class 3 NF T 30-608
○ FIRE CLASS	M0 Certificate available on request
○ HEALTH AND SAFETY	Xi - Irritant - Contains cement Safety data sheet available on request or from www.quickfds.com
○ PACKAGING	15 kg paper bag, 4 kg and 1kg boxes
○ STORAGE	6 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C) and moisture

USE

○ PREPARATION	Gradually pour the powder into water, stirring until a homogeneous paste is obtained Leave the paste to stand
○ DILUTION	45% - i.e. 0.45 litre of water per 1 kg of powder
○ APPLICATION	<ul style="list-style-type: none"> • <i>Equipment</i> Trowel or blade • <i>Conditions</i> Do not apply at temperatures of below +8°C or above +30°C, or at a relative humidity of above 65% HR (hygrometry rate) • <i>Equipment cleaning</i> With water before completely dry
○ SPECIAL RECOMMENDATIONS	Do not stir the paste once it has started to harden
○ APPLICATION THICKNESS	40 mm maximum
○ AVERAGE CONSUMPTION	0.9 kg of powder fills a volume of 1 litre
○ SUBSTRATES	Fine-grain concrete, concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, stone, glass mosaic, old paint substrates Substrates must be hard, cohesive, clean and sound
○ OVERCOAT	Light-weight wall coverings, and interior conventional paint