



N° 1.290



## PRESTONETT® Interior Ready Mixed Quick Dry Fix Tile Adhesive

### GENERAL INFORMATION

#### DESCRIPTION

- Ready Mixed Quick Fix Tile Adhesive

#### INTENDED USE

- Interior
- Suitable for fixing Ceramic tile, polystyrene & gypsum coving

### PRODUCT ADVANTAGES

- ✓ Strong and flexible bond
- ✓ Resistant to humidity
- ✓ Suitable for kitchens and bathrooms
- ✓ White



1

PRESTONETT®



N° 1.290



1

PRESTONETT®

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue: July 2013

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information cannot replace an appropriate description regarding the type and condition of the substrate. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that an updated edition of this sheet has not been issued.



## PRESTONETT® Interior Ready Mixed Quick Dry Fix Tile Adhesive

### TECHNICAL DATA

◉ PRESENTATION	Ready Mixed
◉ COMPONENTS	Based on acrylic copolymers
◉ DENSITY	1.65 +/- 0.1
◉ pH	8 +/- 0.5
◉ COLOUR	White
◉ DRYING TIME	Depending on substrate, temperature and humidity conditions
◉ CLASSIFICATION	EN 12004: 2001 – Type D2E
◉ HEALTH AND SAFETY	Safety data sheet available on request or from <a href="http://www.quickfds.com">www.quickfds.com</a>
◉ PACKAGING	200 ml tube
◉ STORAGE	12 months in original sealed packaging, protected from frost, heat and moisture

### USE

◉ DILUTION	Ready mixed
◉ APPLICATION	Apply in strings or spots separated by 1 cm, or with toothed spatula. Allows corrections within 20 minutes. Not suitable for swimming pools or underwater conditions
• <i>Conditions</i>	Do not apply at temperatures of below +5°C or above +30°C, or at relative humidity of above 65% HR (hygrometry rate)
• <i>Equipment cleaning</i>	With water before completely dry
◉ COVERAGE	Each tube will fix approximately 40 tiles (10cm x 10cm)
◉ SUBSTRATES	Fine-grain concrete, concrete, cellular concrete, gypsum board, cement, concrete block, brick, plaster. Substrates must be hard, cohesive, clean, sound and dry according to the local standards.
◉ SUITABLE FOR FIXING	Ceramic tiles, polystyrene & gypsum coving
◉ TIPS	Remove excess with a damp cloth after 30 mins