



BAG MAX S

GENERAL INFORMATION

Description

Ready mixed spray-applied finishing plaster
Large packaging
Special airless formulation

Intended use

Interior

- For large construction sites
- Finishing substrate



PRODUCT ADVANTAGES

- + Good value for money
- + Smooth application
- + Long working time
- + Apply through, up to 80 m of high pressure hose with appropriate machine

BAG MAX advantages

Reduction in labour time

Remains immobile at the base of the site

Can be contained in a van

No longer necessary to distribute the bags on the sites

Direct access from the exterior : hose up to 80 m

Quick and easy to connect

100% recyclable cardboard

USE

DILUTION	Ready mixed (up to 3% if necessary)
PREPARATION	Mix before use
APPLICATION	
- <i>Conditions</i>	Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.
- <i>Equipment</i>	Smoothing trowel, blade.
- <i>Machine</i>	- Airless machine - 7 l/min (nozzle up to 5.35) Neither strainer nor filter needed for application.
- <i>Connectors</i>	Piston pump or hydraulic pump, "Bag Max" connectors
- <i>Operational mode</i>	1) Fasten the Beissier connector on the Bag Max then on the machine 2) Raise the cover of the Bag Max, open the bag 3) Pull 20 cm of the closing system (blue) placed inside 4) Turn on the machine
- <i>Equipment cleaning</i>	With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.
APPLICATION THICKNESS	2 mm
AVERAGE CONSUMPTION	1 kg/m ²
SUBSTRATES	Concrete, cellular concrete, cement, plaster, plasterboard, old painted substrates. <i>Substrates must be hard, cohesive, clean, sound and dry according to the local standards.</i>
OVERCOAT	Primer, interior conventional paint, light-weight wall coverings.



BAG MAX S

TECHNICAL DATA

COMPONANTS	Polymer base aqueous phase coat mix, mineral fillers, additives.
DENSITY	1.7 ± 0.1
pH	5 ± 1
COLOUR	White
WAITING TIME BEFORE OVERCOATING	Once completely dry
CLASSIFICATION	NF T 36-005 - Family III, class 2
NORM	NF EN 16566
V.O.C	< 1 g/l (Ready mixed)
HEALTH AND SAFETY	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on www.beissier.eu or www.quickfds.com
PACKAGING	500 kg bulk box
STORAGE	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.