



FIX

GENERAL INFORMATION

Description

Binding and sealing solution for chalking, loose & porous substrates

Intended use

Interior
 • For preparing a cohesive & sealed substrate prior to decoration



PRODUCT ADVANTAGES

- + Good in-depth penetration of porous substrates
- + Improve adherence for decorating materials
- + Regulates absorption


USE

DILUTION	Ready mixed
PREPARATION	Mix before use
APPLICATION	
- <i>Conditions</i>	Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.
- <i>Equipment</i>	Brush, paint roller
- <i>Machine</i>	Low pressure sprayer
- <i>Equipment cleaning</i>	With water immediately after use. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.
AVERAGE CONSUMPTION	Roll : 5 to 9 m ² /l
SUBSTRATES	Concrete, cellular concrete, cement, concrete block, brick, plaster, stone. <i>Substrates must be hard, cohesive, clean, sound and dry according to the local standards.</i>
OVERCOAT	Filler, interior conventional paint and light-weight wall coverings.



FIX

TECHNICAL DATA

COMPONANTS	Acrylic copolymer emulsion , selected inorganic fillers.
DENSITY	1 ± 0.1
pH	7.5 ± 0.5
COLOUR	Translucent
ASPECT	Matt, homogeneous
DRYING TIME	Approximately 2 hours
WAITING TIME BEFORE OVERCOATING	Approximately 12 hours
CLASSIFICATION	NF T 36-005 - Family I, class 7b2
V.O.C	< 1 g/l (Ready mixed)
HEALTH AND SAFETY	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on www.beissier.eu or www.quickfds.com
PACKAGING	5 L can
STORAGE	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.