



F - ACÉNIS

GENERAL INFORMATION

Description

Powder fine surface filler
Special air purifying formulation

Intended use

Interior
• Finishing substrates
• Hides small defects



PRODUCT ADVANTAGES

- + Easy to mix
- + Smooth application
- + Wet on wet
- + Long working time
- + Easy to sand
- + Fine

ACÉNIS technology

Cleans the quality of the indoor air

Removes up to 85% of formaldehydes* in the room

Works 24 hours after application

Depollutes even when covered:
compatible with all types of paint,
works even better when
combined with depolluting paint

USE

DILUTION

45% - 0.45 litre of water per 1 kg of powder

PREPARATION

Gradually pour the powder into water, stirring until a homogeneous paste is obtained.

APPLICATION

- Conditions

Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.

- Equipment

Smoothing trowel, blade.

- Equipment cleaning

With water before completely dry. Dispose of any waste material and packaging in an approved waste container or municipal collection point. Do not dispose into the environment.

APPLICATION THICKNESS

1 mm

AVERAGE CONSUMPTION

0.25 kg/m²

SUBSTRATES

Concrete, cement, plaster, plasterboard, old painted substrates.
Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT


Primer, interior conventional paint, light-weight wall coverings.

* According to test report no. 392-2016-00297201-04-05 / 392-2016-00297201-03, carried out by an independent laboratory using the ISO 16000-23 testing protocol



F - ACÉNIS

TECHNICAL DATA

| | |
|--|---|
| COMPONANTS | Plaster base coat mix, organic binder, mineral fillers, additives. |
| pH | 7 ± 0.5 |
| COLOUR | White |
| WORKING TIME AT 20°C | 1 day |
| WAITING TIME BEFORE OVERCOATING | Once completely dry |
| CLASSIFICATION | NF T 36-005 - Family III, class 3 |
| NORM | NF EN 16566 |
| V.O.C | < 0.5 g/l (Ready mixed) |
| HEALTH AND SAFETY |  <p>Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on www.beissier.eu or www.quickfds.com</p> |
| PACKAGING | 25 kg bag |
| STORAGE | 12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging. |

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.