



## INTERIOR DRYWALL JOINT FILLER

### GENERAL INFORMATION

#### Description

Light weight powder drywall joint filler

#### Intended use

Interior

- Taping and jointing plasterboards
- Fixing corner tapes & beads
- Finishing plasterboards



### PRODUCT ADVANTAGES

- + Easy to mix
- + Easy to apply
- + Minimal shrinkage
- + Easy to sand
- + White
- + For all stages of plasterboard jointing & finishing


### USE

<b>DILUTION</b>	55% - 60% - i.e. 0.55 - 0.60 litre of water per 1 kg of powder
<b>PREPARATION</b>	Gradually pour the powder into water, stirring until a homogeneous paste is obtained.
<b>APPLICATION</b>	
- <i>Conditions</i>	Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.
- <i>Equipment</i>	Filling knife, blade, trowel.
- <i>Operational mode</i>	Fill the joint and embed the tape and then cover with product to fully fill the tapered edge board and feather out onto the board. Once dry sand to a smooth surface and apply a second coat feathering out further than the first.
- <i>Equipment cleaning</i>	With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.
<b>APPLICATION THICKNESS</b>	3 mm
<b>AVERAGE CONSUMPTION</b>	0.35 kg/lm
<b>SUBSTRATES</b>	Plasterboard. <i>Substrates must be hard, cohesive, clean, sound and dry according to the local standards.</i>
<b>OVERCOAT</b>	Primer, interior conventional paint, light-weight wall coverings.



# INTERIOR DRYWALL JOINT FILLER

## TECHNICAL DATA

<b>COMPONANTS</b>	Plaster base coat mix, organic binder, mineral fillers, additives.
<b>pH</b>	7 ± 1
<b>COLOUR</b>	White
<b>WORKING TIME AT 20°C</b>	Approximately 1 hour
<b>WAITING TIME BEFORE OVERCOATING</b>	Once completely dry
<b>CLASSIFICATION</b>	NF T 36-005 - Family III, class 3
<b>NORM</b>	NF EN 13 963 - class 3b
<b>V.O.C</b>	< 0.5 g/l (Ready mixed)
<b>HEALTH AND SAFETY</b>	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on <a href="http://www.beissier.eu">www.beissier.eu</a> or <a href="http://www.quickfds.com">www.quickfds.com</a>
<b>PACKAGING</b>	10 kg bag
<b>STORAGE</b>	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.