



## INTERIOR FILLER

### GENERAL INFORMATION

#### Description

Powder filler

#### Intended use

Interior

- Filling holes and cracks of all sizes
- Fixing plaster mouldings, cornices and roses



### PRODUCT ADVANTAGES

- + Does not shrink or crack
- + No thickness limitation
- + Easy to mix
- + Easy to apply
- + Easy to sand
- + White


### USE

<b>DILUTION</b>	50% - i.e. 0.50 litre of water per 1 kg of powder
<b>PREPARATION</b>	Gradually pour the powder into water, stirring until a homogeneous paste is obtained.
<b>APPLICATION</b>	
- <i>Conditions</i>	Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.
- <i>Equipment</i>	Filling knife, blade, smoothing trowel.
- <i>Equipment cleaning</i>	With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.
<b>APPLICATION THICKNESS</b>	Any thickness
<b>AVERAGE CONSUMPTION</b>	1 kg of powder fills a volume of 1 litre
<b>SUBSTRATES</b>	Concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, old painted substrates. <i>Substrates must be hard, cohesive, clean, sound and dry according to the local standards.</i>
<b>OVERCOAT</b>	Primer, interior conventional paint, light-weight wall coverings.



# INTERIOR FILLER

## TECHNICAL DATA

<b>COMPONANTS</b>	Plaster base coat mix, organic binder, mineral fillers, additives.
<b>pH</b>	7 ± 0.5
<b>COLOUR</b>	White
<b>WORKING TIME AT 20°C</b>	Approximately 35 minutes
<b>WAITING TIME BEFORE OVERCOATING</b>	Once completely dry
<b>CLASSIFICATION</b>	NF T 36-005 - Family III, class 3
<b>NORM</b>	NF EN 16566
<b>V.O.C</b>	< 0.5 g/l (Ready mixed)
<b>HEALTH AND SAFETY</b>	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on <a href="http://www.beissier.eu">www.beissier.eu</a> or <a href="http://www.quickfds.com">www.quickfds.com</a>
<b>PACKAGING</b>	2 kg, 1 kg box - 6 kg bag
<b>STORAGE</b>	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.