

## INTERIOR MULTIPURPOSE FILLER

### GENERAL INFORMATION

#### Description

Powder multipurpose filler

#### Intended use

Interior

- Filling holes and cracks
- Levelling and finishing surfaces
- Taping and jointing plasterboards
- Coving adhesive

Use



interior

Application thickness



5 cm

Working time



60 min

Dilution



0,50L  
1kg

Manual application



### PRODUCT ADVANTAGES

- + One product for different jobs
- + Fills up to 5 cm in 1 application
- + Easy to mix
- + Easy to apply
- + Easy to sand
- + No flashing or grinning
- + Brilliant white

### USE

#### DILUTION

50% - i.e. 0.50 litre of water per 1 kg of powder

#### PREPARATION

Gradually pour the powder into water, stirring until a homogeneous paste is obtained.

#### APPLICATION

- *Conditions*

Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.

- *Equipment*

Filling knife, blade, smoothing trowel.

- *Operational mode*

Jointing : fill the joint and embed the tape and then cover with product to fully fill the tapered edge board and feather out onto the board. Once dry sand to a smooth surface and apply a second coat feathering out further than the first.

- *Equipment cleaning*

With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

#### APPLICATION THICKNESS

5 cm

#### AVERAGE CONSUMPTION

1 kg of powder fills a volume of 1 litre

#### SUBSTRATES


Concrete, cellular concrete, cement, concrete block, brick, mortars, plaster, plasterboard, stone, glass cloth, old painted substrates. *Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*

#### OVERCOAT

Primer, interior conventional paint, light-weight wall coverings.

# INTERIOR MULTIPURPOSE FILLER

## TECHNICAL DATA

<b>COMPONANTS</b>	Plaster base coat mix, organic binder, mineral fillers, additives.
<b>pH</b>	Neutral
<b>COLOUR</b>	White
<b>WORKING TIME AT 20°C</b>	60 minutes
<b>WAITING TIME BEFORE OVERCOATING</b>	Once completely dry
<b>CLASSIFICATION</b>	NF T 36-005 - Family III, class 3
<b>NORM</b>	NF EN 13 963 - class 4b
<b>V.O.C</b>	< 0.5 g/l (Ready mixed)
<b>HEALTH AND SAFETY</b>	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on <a href="http://www.beissier.eu">www.beissier.eu</a> or <a href="http://www.quickfds.com">www.quickfds.com</a>
<b>PACKAGING</b>	2 kg , 1 kg box - 15 kg, 5 kg bag
<b>STORAGE</b>	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

