



AIRLISS J LIGHT

GENERAL INFORMATION

Description

Light-weight ready mixed spray-applied plaster, finishing and jointing compound
Special airless formulation

Intended use

Interior

- Taping and jointing plasterboards
- Finishing substrates
- Fixing corner tapes & beads



PRODUCT ADVANTAGES

- + Smooth application
- + Excellent adhesion to substrates
- + Easy to sand
- + Fine finish
- + Manual or mechanical application
- + For all stages of plasterboards jointing and finishing


USE

DILUTION	Ready mixed (up to 3% if necessary)
PREPARATION	Mix before use
APPLICATION	
- <i>Conditions</i>	Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.
- <i>Equipment</i>	Smoothing trowel, blade.
- <i>Machine</i>	- Airless machine - 7 l/min (nozzle up to 5.35) Neither strainer nor filter needed for application. - Bazooka (manual and mechanical application)
- <i>Equipment cleaning</i>	With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.
APPLICATION THICKNESS	3 mm
AVERAGE CONSUMPTION	0.45 kg/ml
SUBSTRATES	Concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, old painted substrates, old sprinkle effect, glass cloth. <i>Substrates must be hard, cohesive, clean, sound and dry according to the local standards.</i>
OVERCOAT	Primer, interior conventional paint, light-weight wall coverings.



AIRLISS J LIGHT

TECHNICAL DATA

COMPONANTS	Polymer base aqueous phase coat mix, mineral fillers, additives.
DENSITY	1.3 ± 0.1
pH	8.5 ± 1
COLOUR	Light grey
WAITING TIME BEFORE OVERCOATING	Once completely dry
CLASSIFICATION	NF T 36-005 - Family III, class 2
NORM	NF T 30-608 NF EN 13963 – class 3A
V.O.C	< 1 g/l (Ready mixed)
HEALTH AND SAFETY	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on www.beissier.eu or www.quickfds.com
PACKAGING	20 kg bucket
STORAGE	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : December 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.