

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING		
1.1. Product identifier		
Product name : HIGH GLOSS FINISHING FILLER		
1.2. Relevant identified uses of the substance or mixture and uses advised against		
For building application		
For professionals and DIY		
Ready Mixed	Interior/Exterior	
1.3. Details of the supplier of the safety data sheet		
Registered company name : BEISSIER SAS.		
Address : Quartier de la gare.77760.LA CHAPELLE LA REINE.FRANCE.		
Telephone : +33 1 60 39 61 10. Fax : +33 1 60 39 61 11.		
beissier.fds@beissier.fr		
www.beissier.fr		
1.4. Emergency telephone number : +33 (0)1 45 42	59 59.	
Association/Organisation : INRS / ORFILA / http://www.centres-antipoison.net.		
Other emergency numbers		
B - Centre Antiposin / Antigifcentrum	Tel: 070/245.245	
CECTION 4 . HAZADDC IDENTIFICATION		
SECTION 2 : HAZARDS IDENTIFICATION		
2.1. Classification of the substance or mixture		
In compliance with EC regulation No. 1272/2008 and its amendments.		
May produce an allergic reaction (EUH208).		

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :EUH208Contains 2-BUTANONE OXIME. May produce an allergic reaction.EUH210Safety data sheet available on request.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

This product doesn't considered like flammable

Avoid inhale solvent vapors.

Avoid contact with the skin.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Preparation based on solvent phase oleo-glycerophtalic dispersion, mineral fillers and additives

Composition :			
Identification	(EC) 1272/2008	Note	%
INDEX: 90622_57_4	GHS08		2.5 <= x % < 10
CAS: 90622-57-4	Dgr		
EC: 292-459-0	Asp. Tox. 1, H304		
	Aquatic Chronic 4, H413		
SOLVANT ISOPARAFFINIQUE ALCANES	EN EUH:066		
C9-C12			
INDEX: 64742_48_9	GHS08		0 <= x % < 2.5
CAS: 64742-48-9	Dgr		
EC: 265-150-3	Asp. Tox. 1, H304		
REACH: 01-2119457273-XXXX	EUH:066		
NAPHTA LOURD HYDROTRAITE			
INDEX: 616-014-00-0	GHS08, GHS05, GHS07	[1]	0 <= x % < 2.5
CAS: 96-29-7	Dgr	[2]	
EC: 202-496-6	Carc. 2, H351		
	Acute Tox. 4, H312		
2-BUTANONE OXIME	Eye Dam. 1, H318		
	Skin Sens. 1, H317		

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

Remove to fresh air

Give nothing by mouth

If the person is unconscious, place in recovery position and call a doctor

Keep patient at rest

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist if it appears pain or visual impairment

In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

- Remove contaminated clothing
- Do not use solvents or thinners

Wash skin thoroughly with water

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist

- multipurpose ABC powder

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Use self-contained breathing apparatus and protective clothing

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Suppress ignition sources and ensure adequate ventilation

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Avoid contact with skin and eyes.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

The product should be used in rooms without flames or sources of ignition. Electrical equipment must be adequately protected.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version : N°4 (16/05/2019) BEISSIER SAS

HIGH GLOSS FINISHING FILLER

In case of contact repeated with skin, use protective cream or gloves.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Keep the container in a well ventilated place

Storage

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Keep away from ignition sources, heat and direct sunlight.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- Germany - AGW (BAuA - TRGS 900, 07/06/2017) :

CAS	VME :	VME :	Excess	Notes
96-29-7		0,3 ppm		8 (I)
		1 mg/m3		

Alkanes C9-C12 (CAS 90622-57-4) : VME = 1200 mg/m3

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation.

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)
- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)
- A2 (Brown)
- A3 (Brown)

Do not breathe vapors

If the air change isn't enough to keep the dusts / vapors below TLV, a suitable respirator must be worn.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties	
General information :	
Physical state :	Viscous liquid.
Odour:	Solvent
Color:	White
Important health, safety and environmental information	
pH :	Not stated.
	Neutral.
Boiling point/boiling range :	Not specified.
Flash point interval :	Not relevant.
Vapour pressure (50°C) :	Below 110 kPa (1.10 bar).
Density :	1.9 +/- 0.1
Water solubility :	Insoluble.
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.
9.2. Other information	
VOC (g/l):	107

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

- Avoid :
- frost
- exposure to light
- heat
- flames and hot surfaces

10.5. Incompatible materials

Keep away from :

- oxidising agents
- acids

- alkalis

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)
- nitrogen oxide (NO)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

No data toxicological available.

Skin corrosion/skin irritation :

A prolonged or repeated contact with skin or mucous membranes may cause irritation, redness, dermatitis ...

Prolonged or repeated contact with the skin may remove the natural fat from the skin.

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

Exposure to solvent vapors above the TLV may result in adverse health effects.

Other information

Monographs on the identification of Carcinogenic hazards to humans (International Agency For Research on Cancer) : CAS 14807-96-6 : Group 3 : Not classifiable as to its carcinogenicity to humans

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

All flow into drains or watercourses should be avoided.

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version : N°4 (16/05/2019) BEISSIER SAS

HIGH GLOSS FINISHING FILLER

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Local arrangements :

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

08 01 11 * waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

- _
- 14.5. Environmental hazards

14.6. Special precautions for user

-

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

- Container information:

No data available.

- Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC) : The permitted European level of VOC in this ready-to-use product is limited to 107 g/l.

The permitted European level of VOC in the ready-to-use product (category IIAi) is 140 g/l maximum (2007/2010).

- Particular provisions :

Keep out of reach of children.

15.2. Chemical safety assessment

No data available.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version : N°4 (16/05/2019) BEISSIER SAS

HIGH GLOSS FINISHING FILLER

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Reference : E0423

Wording of the phrases mentioned in section 3 :

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H351	Suspected of causing cancer.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations :

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.