



PRODUCT ADVANTAGES

- + Anticorrosive
- + Excellent adherence on numerous substrates

PRIMER +

GENERAL INFORMATION

Description

Multipurpose smooth matt primer in solvent phase

Intended use

Interior/exterior
• Allows adherence on numerous substrates

Use



Paint roller application



USE

DILUTION

Ready mixed
Up to 6% of cellulose thinner high aromatic content

PREPARATION

Mix before use

APPLICATION

- *Conditions*

Do not apply at temperatures of below +5°C or above +35°C, or at a relative humidity of above 80% H.R.

- *Equipment*

Brush, paint roller

- *Equipment cleaning*

Cleaning solvent - immediately after use. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

RECOMMENDATIONS

Do not let primer + uncovered more than 3 days.

AVERAGE CONSUMPTION

Roller : 8 to 10 m²/l

SUBSTRATES

Rigid PVC for frames: polyurethane, polyester, polyacrylate and melamine resin, ferrous metals exempt from rust, grease and calamine, metals, wood and by-products
Substrates must be hard, cohesive, clean, sound and dry according to the local standards.



OVERCOAT

Filler, interior conventional paint.



PRIMER +

TECHNICAL DATA

COMPONANTS	Glycerol-modified resins, titanium dioxide, fillers selected.
DENSITY	1.3 ± 0.1
COLOUR	White
ASPECT	Matt
DRYING TIME	Approximately 2 hours
WAITING TIME BEFORE OVERCOATING	Glycerophtalic : 2 hours Cellulose : 12 hours Bi-component Acrylics : 36 hours
CLASSIFICATION	NF T 36-005 - Family I, class 4 a
V.O.C	< 450 g/l (Ready mixed)
HEALTH AND SAFETY	  Contains Hydrocarbons, C9, aromatics Flammable liquid and vapour . May cause respiratory irritation.Toxic to aquatic life with long lasting effects. Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on www.beissier.eu or www.quickfds.com
PACKAGING	2,5 L bucket

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : Juillet 2020

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

STORAGE

36 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.