



PRODUCT ADVANTAGES

- + Smooth application
- + Opacifying
- + Quick drying: recoverable during the day
- + Good levelling properties



PRIM

GENERAL INFORMATION

Description

Drywall primer & sealer

Intended use

Interior

- Stabilizers substrate and improves adhesion
- Absorption regulator



Mechanical application



Airless machine

Paint roller application



USE

DILUTION

Ready mixed
(up to 5% if necessary)

PREPARATION

Mix before use

APPLICATION

- Conditions

Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.

- Equipment

Brush, paint roller

- Machine

Airless machine (nozzle up to 5.15)

- Equipment cleaning

With water immediately after use.
Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

AVERAGE CONSUMPTION

Roll : 8 to 10 m²/l
Airless : 6 to 8 m²/l

SUBSTRATES

Concrete, cement, concrete block, brick, plaster, plasterboard, old painted substrates, glass cloth.
Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT

Plaster, interior conventional paint, light weight wall coverings.




This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : Juillet 2020

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

PRIM

TECHNICAL DATA

COMPONANTS	Acrylic copolymer emulsion with titanium dioxide component.
DENSITY	1.6 ± 0.1
pH	8.5 ± 0.5
COLOUR	White
ASPECT	Matt
DRYING TIME	1 hours
WAITING TIME BEFORE OVERCOATING	6 hours
CLASSIFICATION	NF T 36- 005- Famille I, class 7a2
NORM	NF EN 13 300
V.O.C	≤ 1 g/l (Ready mixed)
HEALTH AND SAFETY	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on www.beissier.eu or www.quickfds.com
PACKAGING	15 L bucket
STORAGE	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.