

## AIRLISS J LIGHT



### GENERAL INFORMATION

#### Description

Light-weight ready mixed spray-applied plaster, finishing and jointing compound  
Special airless formulation

#### Intended use

Interior

- Taping and jointing plasterboards
- Finishing substrates
- Fixing corner tapes & beads



### PRODUCT ADVANTAGES

- + Light product, High efficiency
- + Easy projection and application
- + Easy to sand
- + Fine finish
- + Manual or mechanical application
- + For all stages of plasterboards jointing and finishing

### USE

#### DILUTION

Ready mixed  
(up to 3% for airless / machine use)

#### PREPARATION

Mix before use

#### APPLICATION

##### Conditions

Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.

##### Equipment

Smoothing trowel, blade, banjo

##### Machine

- Airless machine - 5 l/min (nozzle up to 5.31)  
Neither strainer nor filter needed for application.  
- Bazooka (manual and mechanical application)

##### Equipment cleaning

With water before completely dry.  
Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

#### APPLICATION THICKNESS

3 mm

#### AVERAGE CONSUMPTION SUBSTRATES

0.35 kg/ml

Concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, old painted substrates, old sprinkle effect, glass cloth.  
*Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*

#### OVERCOAT


Primer, interior conventional paint, light-weight wall coverings.



## AIRLISS J LIGHT



### TECHNICAL DATA

<b>COMPONANTS</b>	Polymer base aqueous phase coat mix, mineral fillers, additives.
<b>DENSITY</b>	1.2 ± 0.1
<b>pH</b>	8.5 ± 1
<b>COLOUR</b>	White
<b>WAITING TIME BEFORE OVERCOATING CLASSIFICATION</b>	Once completely dry NF T 36-005 - Family III, class 2
<b>NORM</b>	NF T 30-608 NF EN 13963 – class 3A
<b>V.O.C</b>	VOC 2004/42/CE : UE limit value for this product (cat. A/a): 30 g/l - This product contains max 25 g/l VOC
<b>HEALTH AND SAFETY</b>	 <p>Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on <a href="http://www.beissier.eu">www.beissier.eu</a> or <a href="http://www.quickfds.com">www.quickfds.com</a></p>
<b>PACKAGING</b>	20 kg bucket
<b>STORAGE</b>	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : June 2020

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.