

AIRLISS LIGHT



PRODUCT ADVANTAGES

- + Good levelling qualities
- + Easy to apply
- + Easy to sand
- + High quality finish

GENERAL INFORMATION

Description

Lightweight ready mixed, spray-applied plaster

Intended use

Interior
 • Levelling and finishing substrates



USE

DILUTION

Ready mixed
 (up to 3% if necessary)

PREPARATION

Mix before use

APPLICATION

Conditions

Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.

Equipment

Smoothing trowel, blade.

Machine

Airless machine - 5 l/min (nozzle up to 5.35)
 Neither strainer nor filter needed for application.

Equipment cleaning

With water before completely dry.
 Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

APPLICATION THICKNESS

3 mm

AVERAGE CONSUMPTION

0.45 kg/ml

SUBSTRATES

Concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, old painted substrates, glass cloth.
Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT

Primer, interior conventional paint, light-weight wall coverings.

AIRLISS LIGHT



TECHNICAL DATA

COMPONANTS Polymer base aqueous phase coat mix, mineral fillers, additives.

DENSITY 1.3 ± 0.1

pH 8.5 ± 1

COLOUR White

WAITING TIME BEFORE OVERCOATING Once completely dry

CLASSIFICATION NF T 36-005 - Family III, class 2

NORM NF T 30-608
NF EN 13963 – class 3A

V.O.C < 1 g/l (Ready mixed)

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING 15 L bag

STORAGE 12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.