



## PRODUCT ADVANTAGES

- + Excellent isolation properties
- + Without tension
- + Resists wet abrasion: class 2
- + Can be used to over coat distemper



# HIMALAYA AGUA

## GENERAL INFORMATION

### Description

A stain blocking primer

### Intended use

Interior  
• Cover old stained substrates

Use



Mechanical application



Airless machine

Paint roller application



## USE

### DILUTION

Ready mixed  
(up to 5% if necessary)

### PREPARATION

Mix before use

### APPLICATION

- *Conditions*

Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.

- *Equipment*

Brush, paint roller

- *Machine*

Airless machine (nozzle from 5.17)

- *Equipment cleaning*

With water immediately after use. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

### AVERAGE CONSUMPTION

Roll : 9 to 11 m<sup>2</sup>/l  
Airless : 6 to 8 m<sup>2</sup>/l

### RECOMMENDATION

For optimal stain insulation, wait 6 hours between 2 layers.

### SUBSTRATES

Concrete, cellular concrete, cement, concrete block, plaster, plasterboard, old painted substrates, primed wood, glass cloth.

*Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*


### OVERCOAT

Filler, interior conventional paint, light-weight wall coverings.

# HIMALAYA AGUA

## TECHNICAL DATA



<b>COMPONANTS</b>	Acrylic copolymer emulsion, selected inorganic fillers.
<b>DENSITY</b>	1.4 ± 0.1
<b>pH</b>	8.5 ± 0.5
<b>COLOUR</b>	White
<b>ASPECT</b>	Matt
<b>DRYING TIME</b>	2 hours
<b>WAITING TIME BEFORE OVERCOATING</b>	6 to 12 hours
<b>CLASSIFICATION</b>	NF T 36-005 - Family I, class 7a2
<b>NORM</b>	NF EN 13 300
<b>V.O.C</b>	≤ 1 g/l (Ready mixed)
<b>HEALTH AND SAFETY</b>	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on <a href="http://www.beissier.eu">www.beissier.eu</a> or <a href="http://www.quickfds.com">www.quickfds.com</a>
<b>PACKAGING</b>	15 L, 5 L bucket
<b>STORAGE</b>	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

**Date of issue** : Juillet 2020

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.