



GT

GENERAL INFORMATION

Description

Ready mixed spray-applied plaster and decorative coating with sprinkle effect

Intended use

Interior
• Finishing substrates (smooth or sprinkle/textured effects)



PRODUCT ADVANTAGES

- + Can be hand-floated to create decorative effects
- + Can be tinted upon request with water base colourants during the production process
- + White


USE

DILUTION	Ready mixed (up to 3% if necessary)
PREPARATION	Mix before use
APPLICATION	
<i>Conditions</i>	Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.
<i>Equipment</i>	Smoothing trowel, blade, trowel.
<i>Machine</i>	Spray machine (nozzle up to 5 mm)
<i>Equipment cleaning</i>	With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.
APPLICATION THICKNESS	1 mm
AVERAGE CONSUMPTION	1 to 1.5 kg/m ²
SUBSTRATES	Concrete, cellular concrete, cement, brick, plaster, plasterboard, old painted substrates. <i>Substrates must be hard, cohesive, clean, sound and dry according to the local standards.</i>
OVERCOAT	Primer, interior conventional paint, light-weight wall coverings, varnish, wax.





TECHNICAL DATA

COMPONANTS	Polymer base aqueous phase coat mix, mineral fillers, additives.
DENSITY	1.7 ± 0.1
pH	8 ± 1
COLOUR	White
WAITING TIME BEFORE OVERCOATING	Once completely dry
CLASSIFICATION	NF T 36-005 - Family III, class 2
NORM	NF EN 16566
V.O.C	< 1 g/l (Ready mixed)
HEALTH AND SAFETY	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on www.beissier.eu or www.quickfds.com
PACKAGING	25 kg bag
STORAGE	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : May 2021

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.