

WOOD FILLER

GENERAL INFORMATION

Description

Ready mixed wood filler

Intended use

- Interior/exterior
- Filling small holes and cracks
 - Repairing minor imperfections



Use



Application
thickness



Working
time



Dilution



Manual
application

PRODUCT ADVANTAGES

- + Easy to apply
- + Excellent adhesion to substrates
- + Up to 1cm thickness
- + Easy to sand
- + Fine finish

USE

DILUTION

Ready mixed

APPLICATION

Conditions

Do not apply at temperatures of below +5°C or above +35°C, or at a relative humidity of above 80% H.R.

Equipment

Filling knife, blade

Equipment cleaning

With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

RECOMMENDATIONS

On soft or friable wood, it is advised to apply a wood hardener.

APPLICATION THICKNESS

1 cm

AVERAGE CONSUMPTION

0.5 kg/m²

SUBSTRATES

Most types of wood including chipboard, plywood and exotic species.
Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT


Wood stains, varnishes, primers and conventional interior & exterior paints.



WOOD FILLER



TECHNICAL DATA

COMPONANTS	Polymer base aqueous phase coat mix, mineral fillers, additives.
DENSITY	1,7 ± 0,1
pH	8 ± 1
COLOUR	Beige
WORKING TIME AT 20°C	Unlimited
WAITING TIME BEFORE OVERCOATING	Approximately 12 h at 5 mm thickness
CLASSIFICATION	NF T 36-005 - Family IV, class 4b
NORM	NF EN 16566
V.O.C	< 1 g/l (Ready mixed)
HEALTH AND SAFETY	 <p>Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on www.beissier.eu or www.quickfds.com</p>
PACKAGING	1 kg
STORAGE	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : February 2019

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.