

HIGH GLOSS FINISHING FILLER



GENERAL INFORMATION

Description

Ready mixed high gloss surface filler

Intended use

- Interior/ exterior
- Very smooth & hard finish
 - Corrects small defects
 - Ideal for wood renovation



PRODUCT ADVANTAGES

- + Very fine glass like finish
- + Excellent adhesion to substrates
- + Enhance the paint finish
- + Easy to apply

USE

DILUTION

Ready mixed

APPLICATION

Conditions

Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.

Equipment

Blade, trowel.

Equipment cleaning

With solvent before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

APPLICATION THICKNESS

0,5 mm

AVERAGE CONSUMPTION

0.15 kg/m²

SUBSTRATES

Plaster, plasterboard, primed wood, old painted substrates.
Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT

Interior or exterior conventional paint, lacquer



HIGH GLOSS FINISHING FILLER



TECHNICAL DATA

COMPONANTS Oleo Glycerophtalic resins

DENSITY 1.9 ± 0.1

COLOUR White

WORKING TIME AT 20°C Unlimited

WAITING TIME BEFORE OVERCOATING Once completely dry

CLASSIFICATION NF T 36-005 - Family III, class 1

NORM NF EN 16566

V.O.C < 20 g/l (Ready mixed)

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves.

Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING 5kg, 1 kg bucket

STORAGE 12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : May 2019

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.