



INTERIOR QUICK DRY FILLER

GENERAL INFORMATION

Description

Quick drying-powder filler

Intended use

Interior

- Filling holes and cracks of up to 4cm
- Particularly suitable for renovation work



PRODUCT ADVANTAGES

- + Can be applied on damp substrates
- + Easy sand
- + Excellent adhesion to many substrates
- + Can be overcoated after just 3 hours
- + Does not shrink or crack
- + Brilliant white

USE

DILUTION	45% - i.e. 0.45 litre of water per 1 kg of powder
PREPARATION	Gradually pour the powder into water, stirring until a homogeneous paste is obtained
APPLICATION	
<i>Conditions</i>	Do not apply at temperatures of below +8°C or above +30°C, or at a relative humidity of above 65% H.R (hygrometry rate)
<i>Equipment</i>	Trowel or blade
<i>Equipment cleaning</i>	With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.
RECOMMENDATIONS	Do not stir the paste once it has started to harden
APPLICATION THICKNESS	4 cm
AVERAGE CONSUMPTION	0.9 kg of powder fills a volume of 1 litre
SUBSTRATES	Fine-grain concrete, concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, stone, glass mosaic, old paint substrates <i>Substrates must be hard, cohesive, clean, sound and dry according to the local standards</i>
OVERCOAT	Light-weight wall coverings, and interior conventional paint

INTERIOR QUICK DRY FILLER



TECHNICAL DATA

COMPONANTS Syntetic resin and hydraulic blinders
Selected inorganic fibres and fillers

pH On mixing : 11 ± 1
After drying : 9 ± 1

COLOUR White

WORKING TIME AT 20°C Approximately 30 minutes

WAITING TIME BEFORE OVERCOATING Approximately 3 hours at 20°C

CLASSIFICATION NF T 36-005 - Family III, class 3
NF T 30-608

V.O.C < 20 g/l (Ready mixed)

HEALTH AND SAFETY



Danger - Contains cement
Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves.
Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING 5 kg bag

STORAGE 12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : October 2019

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.