

## PRO ROLL

### GENERAL INFORMATION

#### Description

Levelling powder

#### Intended use

Interior

- For levelling and finishing substrates



### USE

#### DILUTION

Ready mixed

#### PREPARATION

Mix before use

#### APPLICATION

- *Conditions*

Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.

- *Equipment*

Smoothing trowel, blade.

- *Equipment cleaning*

With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

#### APPLICATION THICKNESS

5 mm

#### AVERAGE CONSUMPTION

1 kg/m<sup>2</sup>

#### SUBSTRATES

Concrete, cellular concrete, cement, concrete, block, brick, plaster, plasterboard, old painted substrates, old sprinkle effect, glass cloth. *Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*

#### OVERCOAT

Primer, interior conventional paint, light-weight wall coverings.

### PRODUCT ADVANTAGES

- + Smooth application
- + Good levelling qualities
- + Easy to sand
- + Fine finish

### Roller Application

Rapidity  
Comfort  
Simplicity



# PRO ROLL



## TECHNICAL DATA

**COMPONANTS** Polymer base aqueous phase coat mix, mineral fillers, additives.

**pH** 1.7 ± 0.1

**COLOUR** White

**WORKING TIME AT 20°C** Unlimited

**WAITING TIME BEFORE OVERCOATING** Once completely dry

**CLASSIFICATION** NF T 36-005 - Family III, class 2

**NORM** NF EN 16566

**V.O.C** < 0.5 g/l (Ready mixed)

### HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on [www.beissier.eu](http://www.beissier.eu) or [www.quickfds.com](http://www.quickfds.com)

**PACKAGING** 15 kg bucket

**STORAGE** 12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.