



INT/EXT READY MIXED WOOD FILLER

GENERAL INFORMATION

Description

Ready mixed wood filler

Intended use

Interior/exterior

- Filling holes & cracks on doors, window frames, skirting boards & floor boards



PRODUCT ADVANTAGES

- + Flexible
- + Fibre glass reinforced
- + Quick drying
- + Easy to sand
- + Easy to apply
- + Suitable for use on most types of wood

USE

DILUTION

Ready mixed

APPLICATION

- *Conditions*

Do not apply at temperatures of below +5°C or above +35°C, or at a relative humidity of above 80% H.R.

- *Equipment*

Blade, filling knife.

- *Operational mode*

Massage tube before application. Work the filler in to the repair and leave slightly proud for sanding. For deep repairs fill in two or more layers. Once dry sand and then stain, varnish or paint.

- *Equipment cleaning*

With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

RECOMMENDATIONS

Exterior use : the filler must be over coated with a weather proof stain, varnish or paint. Do not apply on damp wood.

APPLICATION THICKNESS

5 mm

AVERAGE CONSUMPTION

125 ml/m²/mm thickness

SUBSTRATES

Most types of wood, chipboard, plywood, ceramic tiles.
Substrates must be hard, cohesive, clean, sound and dry according to the local standards.


OVERCOAT

Primer, stain, varnish, paint.



INT/EXT READY MIXED WOOD FILLER

TECHNICAL DATA

COMPONANTS	Acrylic Polymers
DENSITY	1.5 ± 0.1
pH	7.5 ± 8.5
COLOUR	White, Natural, Medium, Dark
WORKING TIME AT 20°C	Unlimited
WAITING TIME BEFORE OVERCOATING	1 - 4 hours
CLASSIFICATION	NF T 36-005 - Family IV, class 3
V.O.C	< 20 g/l (Ready mixed)
HEALTH AND SAFETY	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on www.beissier.eu or www.quickfds.com
PACKAGING	125 ml tube
STORAGE	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.