

STABILISING SOLUTION



GENERAL INFORMATION

Description

Penetrating primer for chalky & weathered surfaces

Intended use

Interior/Exterior
 • For preparing a cohesive & sealed substrate prior to decoration

Paint roller application



Mechanical application



Low pressure sprayer

Use



Product advantages

- + Stabilises poor surfaces prior to decorating
- + Regulates porosity
- + Consolidates Chalky Surfaces
- + Quick Drying

USE

DILUTION Delivery viscosity

PREPARATION Mix before use

APPLICATION

Conditions Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above 70% H.R.

Equipment Brush, paint roller

Machine Low pressure sprayer

Equipment cleaning With water immediately after use.

Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

AVERAGE CONSUMPTION Roll : 5 to 9 m²/l

SUBSTRATES Concrete, cellular concrete, cement, concrete block, brick, plaster, stone, render.

Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT Filler, plaster, interior/exterior conventional paints and light weight wall coverings.

STABILISING SOLUTION



TECHNICAL DATA

COMPONANTS	Acrylic copolymer emulsion , selected inorganic fillers.
DENSITY	1 ± 0.1
pH	7.5 ± 0.5
COLOUR	Translucent
ASPECT	Matt Finish
DRYING TIME	Approximately 2 hours
WAITING TIME BEFORE OVERCOATING	Approximately 12 hours
CLASSIFICATION	NF T 36-005 - Family I, class 7b2
V.O.C	< 1 g/l (Ready mixed)

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING 5 L can

STORAGE 12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : March 2019

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.