

AIRLISS EXT



GENERAL INFORMATION

Description

Ready mixed spray-applied leveller
Special airless formulation

Intended use

Exterior
• Suitable for finishing the undersides of balcony slabs before decoration
• Suitable for levelling contraction/control joints in concrete



PRODUCT ADVANTAGES

- + Excellent adhesion to substrates
- + Good levelling qualities
- + Smooth application
- + Easy to sand
- + Manual or mechanical application
- + Water and humidity resistant
- + Water vapour permeable

USE

DILUTION

Ready mixed
(up to 3% if necessary)

PREPARATION

Mix before use

APPLICATION

Conditions

Do not apply at temperatures of below +5°C or above +35°C, or at a relative humidity of above 80% H.R.

Equipment

Smoothing trowel, blade.

Machine

- Airless machine - 5 l/min (nozzle up to 5.35)

Neither strainer nor filter needed for application.

- Spray machine (nozzle up to 6 mm)

Equipment cleaning

With water before completely dry.

Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

APPLICATION THICKNESS

5 mm

AVERAGE CONSUMPTION SUBSTRATES

1 to 3 kg/m²

Concrete, cement, concrete block, old painted substrates. *Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*

OVERCOAT

Exterior paint (thin film, thick plastic coating, water proofing coating)



AIRLISS EXT



This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : June 2020

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

TECHNICAL DATA

COMPONANTS	Polymer base aqueous phase coat mix, mineral fillers, additives.
DENSITY	1.55 ± 0.1
pH	8 ± 1
COLOUR	Grey
WAITING TIME BEFORE OVERCOATING	Once completely dry
CLASSIFICATION	NF T 36-005 - Family IV, class 4b
NORM	NF EN 16566
V.O.C	VOC 2004/42/CE : UE limit value for this product (cat. A/a): 30 g/l - This product contains max 25 g/l VOC

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING 25 kg bag - 25 kg bucket

STORAGE 12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.