



## Advantages

- + Suitable for use with all automated taping and jointing tools
- + Smooth application
- + Excellent adhesion to substrates
- + Easy to sand
- + Fine finish
- + Manual or mechanical application
- + For all stages of plasterboards jointing and finishing
- + White



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



# AIRLISS J

## GENERAL INFORMATION

### Description

Ready mixed spray-applied plaster, finishing and jointing compound  
Special airless formulation

### Intended use

- Interior
- Taping and jointing plasterboards
- Finishing substrates
- Fixing corner tapes & beads

Manual application



Banjo



Use



interior

Application thickness



3 mm

Ready mixed

Mechanical application



Airless machine

Roller application



## USE

**DILUTION** ..... Ready mixed

**PREPARATION** ..... Stir before use (dilute up to 3% if necessary)

### APPLICATION

**Conditions** ..... Do not apply at temperatures of below 8°C or above 35°C, or at a relative humidity of above 70% H.R.

**Equipment** ..... Smoothing trowel, blade, banjo, dedicated roller

**Machine** ..... Airless machine - 5 l/min:

- Joint filling: Add the brackets (tip size up to 3.33).
- Finishing application: (nozzle up to Neither strainer nor filter needed for application.
- Neither strainer nor filter needed for application.
- Bazouka (manual or mechanical application)

**Operational mode** ..... 1-Apply plaster liberally in the recess between the bevelled edges of the boarding.  
2-Place ground (or labelled) side of the joint tape on the plaster.  
3-Press joint tape into place and remove surplus plaster.  
4-Using a float, smooth over the joint tape with plaster.  
5-Leave plaster layer to dry.  
6-Finishing layer of plaster to the joint with a trowel. This finishing layer should be applied to 5 cm beyond the slope of the board edges on either side.

**Equipment cleaning** ..... With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

**APPLICATION THICKNESS** ..... 3 mm

**AVERAGE CONSUMPTION** ..... Finishing application: 1 kg/m<sup>2</sup>  
Joint strip application: 0,45 kg/lm

**SUBSTRATES** ..... Plasterboard.

*Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*

**OVERCOAT** ..... Primer, interior conventional paint, light-weight wall coverings.



## AIRLISS J

### TECHNICAL DATA

<b>COMPONANTS</b> .....	Polymer base aqueous phase coat mix, mineral fillers, additives. 97 % of raw materials of natural origin (Calcium carbonate, talc, water, clay, starch)
<b>DENSITY</b> .....	1,7 ± 0,1
<b>pH</b> .....	8 ± 0,5
<b>COLOUR</b> .....	White
<b>WAITING TIME BEFORE OVERCOATING</b> .....	Once completely dry
<b>CLASSIFICATION</b> .....	NF T 36-005 - Family III, class 2
<b>NORM</b> .....	NF EN 13963 - type 3A NF EN 16566
<b>V.O.C.</b> .....	< 1 g/l (ready mixed)

### HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. During application by projection, wearing glasses and a mask is recommended. Safety data sheet available on [www.beissier.eu](http://www.beissier.eu) or [www.quickfds.com](http://www.quickfds.com)

<b>PACKAGING</b> .....	25 kg bucket
<b>STORAGE</b> .....	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. + 30°C) sun and moisture. Close well after use. Store in original packaging

0380	<b>UK CA</b>	21	Jointing materials for gypsum plasterboards EN 13963 : 2014 Type 3A
			BAGAR AIRLISS J - DOP UKCA EN 75018-007 V1
BEISSIER - Quartier de la gare - 77760 LA CHAPELLE LA REINE FRANCE			
Reaction to fire		A2-s1, d0	
Flexural Strength		NPD	

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : February 2024

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

# Beissier

Applying excellence

BEISSIER | Becket House - 1 Lambeth Palace Road - LONDON - SE1 7EU

Customer service : ☎ 020 7092 6696 | [contact@beissier.eu](mailto:contact@beissier.eu)