



AIRLISS J LIGHT

GENERAL INFORMATION

Description

Light-weight ready mixed spray-applied plaster, finishing and jointing compound
Special mechanical application

Intended use

- Interior
- Taping and jointing plasterboards
- Finishing substrates
- Fixing corner tapes & beads

Manual application



Banjo



Use



interior

Application thickness



3 mm

Ready mixed

Mechanical application



Airless machine

Roller application



Advantages

- + Suitable for use with all automated taping and jointing tools
- + Light product, High efficiency
- + Easy projection and application
- + Easy to sand
- + Fine finish
- + Manual or mechanical application
- + For all stages of plasterboards jointing and finishing



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



USE

DILUTION Ready mixed
(up to 3% for airless machine use)

PREPARATION Stir before use (dilute up to 3% if necessary)

APPLICATION

Conditions Do not apply at temperatures of below 8°C or above 35°C, or at a relative humidity of above 70% H.R.

Equipment Smoothing trowel, blade, banjo, dedicated roller Machine

Machine Airless machine - 5 l/min:
- Joint filling: Add the brackets (tip size up to 3.33).
- Finishing application: Add the brackets (tip size up to 5.31).
Neither strainer nor filter needed for application.

Equipment cleaning With water before completely dry.
Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

APPLICATION THICKNESS 3 mm

AVERAGE CONSUMPTION Finishing application: 0,7 kg/m²
Joint strip application: 0,35 kg/lm

SUBSTRATES Plasterboard.

Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT Primer, interior conventional paint, light-weight wall coverings.

AIRLISS J LIGHT



TECHNICAL DATA

| | |
|--|--|
| COMPONANTS | Polymer base aqueous phase coat mix, mineral fillers, additives. 93 % of raw materials of natural origin (Calcium carbonate, water, clay, starch) |
| DENSITY | 1,2 ± 0,1 |
| pH | 8,5 ± 0,5 |
| COLOUR | White |
| WAITING TIME BEFORE OVERCOATING | Once completely dry |
| CLASSIFICATION | NF T 36-005 - Family III, class 2 |
| NORM | NF EN 13963 - type 3A NF EN 16566 |
| V.O.C. | < 1 g/l (ready mixed) |

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. During application by projection, wearing glasses and a mask is recommended. Safety data sheet available on www.beissier.eu or www.quickfds.com

| | |
|------------------------|--|
| PACKAGING | 18 kg bucket |
| STORAGE | 12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. + 30°C) sun and moisture. Close well after use. Store in original packaging |

| | | | |
|--|------------------|-----------|--|
| 0380 | UK CA | 21 | Jointing materials for gypsum plasterboards EN 13963 : 2014 Type 3A |
| | | | BAGAR AIRLISS J LIGHT - DOP UKCA EN 75030-003 V1 |
| BEISSIER - Quartier de la gare - 77760 LA CHAPELLE LA REINE FRANCE | | | |
| Reaction to fire | | A2-s1, d0 | |
| Flexural Strength | | NPD | |

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : February 2024

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

Beissier

Applying excellence

BEISSIER | Becket House - 1 Lambeth Palace Road - LONDON - SE1 7EU

Customer service : ☎ 020 7092 6696 | contact@beissier.eu