

# EXTERIOR QUICK DRY FILLER



## GENERAL INFORMATION

### Description

Powder quick-drying filler

### Intended use

- Exterior
- Filling holes and cracks of up to 4 cm
- Renovation work

Manual application



Use



Application thickness



Working time



Dilution



## Advantages

- + Excellent adhesion to substrates
- + Can be overcoated after just 3 hours
- + Does not shrink or crack
- + Water vapour permeable
- + Can be applied to damp substrates
- + Fibre enriched
- + Lump free mixing
- + Sameday = apply, sand & paint
- + White

## USE

**DILUTION** ..... 45% - i.e. 0,45 liter of water per 1 kg of powder

**PREPARATION** ..... Gradually pour the powder into the water, mixing until a homogeneous paste is obtained.

### APPLICATION

**Conditions** ..... Do not apply at temperatures of below + 5°C or above + 35°C, or at a relative humidity above 80% H.R

**Equipment** ..... Filling knife, blade

**Equipment cleaning** ..... With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

**APPLICATION THICKNESS** ..... 40 mm

**AVERAGE CONSUMPTION** ..... 0,9 kg of powder fills a volume of 1 liter



**SUBSTRATES** ..... Concrete, cellular concrete, cement, concrete block, brick, stone, plaster, mortars, old painted substrates. *Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*

**OVERCOAT** ..... Exterior paint (thin film, thick plastic coating, waterproofing coating), epoxide, polyurethane.



## EXTERIOR QUICK DRY FILLER

### TECHNICAL DATA

<b>COMPONANTS</b> .....	Cement base coat mix, organic binder, fibres, mineral fillers, additives 25% of raw materials of natural origin (Calcium carbonate, sand)
<b>pH</b> .....	On mixing : 11 ± 1 After drying : 9 ± 1
<b>COLOUR</b> .....	White
<b>WORKING TIME AT 20°C</b> .....	Approximately 35 minutes
<b>WAITING TIME BEFORE OVERCOATING</b> .....	Approximately 3 hours at 20°C 55% H.R. (for 4 cm thickness)
<b>CLASSIFICATION</b> .....	NF T 36-005 - Family IV, class 4c
<b>NORM</b> .....	NF EN 16566 NF ENVIRONNEMENT : Enduits de peinture - NF 446 The certified characteristics are available from AFNOR Certification 11 rue de Pressensé 93571 La Plaine Saint-Denis Cedex - France or on <a href="http://www.ecolabels.fr">www.ecolabels.fr</a>
<b>V.O.C.</b> .....	< 0,5 g/l (ready mixed)
<b>HEALTH AND SAFETY</b> .....	  Danger - contains cement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Avoid breathing dust. Wear suitable gloves and glasses. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Safety data sheet available on <a href="http://www.beissier.eu">www.beissier.eu</a> or <a href="http://www.quickfds.com">www.quickfds.com</a>
<b>PACKAGING</b> .....	1 kg box and 6 kg bag
<b>STORAGE</b> .....	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. + 30°C) sun and moisture. Close well after use. Store in original packaging

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : January 2024

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

# Beissier

Applying excellence

BEISSIER | Becket House - 1 Lambeth Palace Road - LONDON - SE1 7EU

Customer service : ☎ 020 7092 6696 | [contact@beissier.eu](mailto:contact@beissier.eu)