



## Advantages

- + Will not shrink, crack or slump
- + No thickness limitation
- + No flashing or grinning
- + Lump free easy mix
- + Easy to apply
- + Easy to sand
- + White

# INTERIOR FILLER

## GENERAL INFORMATION

### Description

Powder filler

### Intended use

- Interior
- Filling holes and cracks

Manual application



Use



Application thickness



Working time



Dilution



## USE

**DILUTION** ..... 50% - i.e. 0,50 liter of water per 1 kg of powder

**PREPARATION** ..... Gradually pour the powder into the water, mixing until a homogeneous paste is obtained.

### APPLICATION

**Conditions** ..... Do not apply at temperatures of below + 8°C or above + 35°C, or at a relative humidity above 70% H.R

**Equipment** ..... Filling knife, blade

**Equipment cleaning** ..... With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

**APPLICATION THICKNESS** ..... Any thickness

**AVERAGE CONSUMPTION** ..... 1 kg of powder fills a volume of 1 liter

**SUBSTRATES** ..... Concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, old painted substrates. *Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*

**OVERCOAT** ..... Primer, filler, conventional paint, light-weight wall coverings.



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



## INTERIOR FILLER

### TECHNICAL DATA

|  |   |
|--|---|
| <b>COMPONANTS</b> .....                      | Plaster base coat mix, organic binder, mineral fillers, additives<br>99% of raw materials of natural origin (Natural plaster, calcium carbonate, gypsum, gelatin, starch)   |
| <b>pH</b> .....                              | 7 ± 0.5   |
| <b>COLOUR</b> .....                          | White   |
| <b>WORKING TIME AT 20°C</b> .....            | Approximately 35 minutes  |
| <b>WAITING TIME BEFORE OVERCOATING</b> ..... | Once completely dry   |
| <b>CLASSIFICATION</b> .....                  | NF T 36-005 - Family III, class 3   |
| <b>NORM</b> .....                            | NF EN 16566<br>NF ENVIRONNEMENT :<br>Enduits de peinture - NF 446<br>The certified characteristics are available from AFNOR Certification<br>11 rue de Pressensé 93571<br>La Plaine Saint-Denis Cedex - France<br>or on <a href="http://www.ecolabels.fr">www.ecolabels.fr</a>  |
| <b>V.O.C.</b> .....                          | < 0,1 g/l (ready mixed)   |
| <b>HEALTH AND SAFETY</b> .....               | <br>Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Do not breathe dust.<br>Safety data sheet available on <a href="http://www.beissier.eu">www.beissier.eu</a> or <a href="http://www.quickfds.com">www.quickfds.com</a> |
| <b>PACKAGING</b> .....                       | 2 kg and 1 kg box - 6 kg bag  |
| <b>STORAGE</b> .....                         | 12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. + 30°C) sun and moisture. Close well after use. Store in original packaging  |

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : January 2024

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

# Beissier

Applying excellence

BEISSIER | Becket House - 1 Lambeth Palace Road - LONDON - SE1 7EU

Customer service : ☎ 020 7092 6696 | [contact@beissier.eu](mailto:contact@beissier.eu)