

## LIGHT WEIGHT FILLER



### Advantages

- + Excellent adhesion to substrates
- + Fills & finishes in a single pass
- + No thickness limitations
- + Very easy to sand
- + Does not shrink or crack
- + Very fine finish
- + Brillant white



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

### GENERAL INFORMATION

#### Description

Light weight ready mixed filler

#### Intended use

- Interior/exterior
- Filling holes and cracks of all sizes

Manual application



Use



interior/  
exterior

Application thickness



Any  
thickness

Working time



Unlimited

Ready mixed

### USE

**DILUTION** ..... Ready mixed

#### APPLICATION

**Conditions** ..... Do not apply at temperatures of below + 5°C or above + 35°C, or at a relative humidity of above 80% H.R.

**Equipment** ..... Filling knife, blade

**Equipment cleaning** ..... With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

**APPLICATION THICKNESS** ..... Any thickness

**AVERAGE CONSUMPTION** ..... 1L/m<sup>2</sup>/mm thickness

**SUBSTRATES** ..... Concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, previously printed wood, old painted substrates.

*Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*

**OVERCOAT** ..... Primer, filler, conventional paint, light-weight wall coverings



## LIGHT WEIGHT FILLER

### TECHNICAL DATA

<b>COMPONANTS</b> .....	Polymer base aqueous phase coat mix, mineral fillers, additives
<b>DENSITY</b> .....	0,4 ± 0,05
<b>pH</b> .....	8,5 ± 1
<b>COLOUR</b> .....	White
<b>WORKING TIME AT 20°C</b> .....	Unlimited
<b>WAITING TIME BEFORE OVERCOATING</b> .....	Once completely dry
<b>CLASSIFICATION</b> .....	NF T 36-005 - Family IV, class 4b
<b>NORM</b> .....	NF EN 16566
<b>V.O.C.</b> .....	< 0,5 g/l (ready mixed)

### HEALTH AND SAFETY .....



Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on [www.beissier.eu](http://www.beissier.eu) or [www.quickfds.com](http://www.quickfds.com)

**PACKAGING** .....

750 ml and 250 ml bucket

### STORAGE .....

12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. + 30°C) sun and moisture. Close well after use. Store in original packaging

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : January 2024

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

# Beissier

Applying excellence

BEISSIER | Becket House - 1 Lambeth Palace Road - LONDON - SE1 7EU

Customer service : ☎ 020 7092 6696 | [contact@beissier.eu](mailto:contact@beissier.eu)