



MULTIPURPOSE FILLER

GENERAL INFORMATION

Description

Powder multipurpose filler

Intended use

- Interior

- Filling holes and cracks
- Levelling and finishing surfaces
- Taping and jointing plasterboards
- Coving adhesive

Manual application



Use



Application thickness



Working time



Dilution



Advantages

- + The «All-in-one» for internal repairs
- + Fills up to 5 cm in 1 application
- + Will not shrink, crack or slump
- + No flashing or grinning
- + Easy to mix
- + Easy to apply
- + Easy to sand
- + Brilliant white

USE

DILUTION 50% - i.e. 0,50 liter of water per 1 kg of powder

PREPARATION Gradually pour the powder into the water, mixing until a homogeneous paste is obtained.

APPLICATION

Conditions Do not apply at temperatures of below + 8°C or above + 35°C, or at a relative humidity above 70% H.R.

Equipment Filling knife, blade, smoothing trowel

Equipment cleaning With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

APPLICATION THICKNESS 50 mm

AVERAGE CONSUMPTION 1 kg/m²

SUBSTRATES Concrete, cellular concrete, cement, concrete block, brick, mortars, plaster, plasterboard, stone, glass cloth, old painted substrates.

Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT Primer, filler, conventional paint, light-weight wall coverings.



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



MULTIPURPOSE FILLER

TECHNICAL DATA

COMPONANTS	Plaster base coat mix, organic binder, mineral fillers, additives 20% of raw materials of natural origin (Calcium carbonate)
pH	8 ± 1
COLOUR	White
WORKING TIME AT 20°C	Approximately 60 minutes
WAITING TIME BEFORE OVERCOATING	Once completely dry
CLASSIFICATION	NF T 36-005 - Family III, class 3 NF EN 13 963 – Type 4B
V.O.C.	< 0,5 g/l (ready mixed)

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Do not breathe dust. Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING

1 kg box and 5 kg bag

STORAGE

12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. + 30°C) sun and moisture. Close well after use. Store in original packaging

	Jointing materials for gypsum plasterboards EN 13963 : 2014 Type 4B
	PRESTONETT MULTIPURPOSE FILLER
BEISSIER - Quartier de la gare - 77760 LA CHAPELLE LA REINE FRANCE	
Reaction to fire	A2-s1, d0
Flexural Strength	NPD

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : January 2024

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

Beissier

Applying excellence

BEISSIER | Becket House - 1 Lambeth Palace Road - LONDON - SE1 7EU

Customer service : ☎ 020 7092 6696 | contact@beissier.eu