



Advantages

- + Ready to sand & paint in 15 min
- + Excellent adhesion to substrates
- + Water and humidity resistant
- + White

QUICK DRY FILLER

GENERAL INFORMATION

Description

Ready mixed quick dry filler

Intended use

- Interior/exterior
- Minor surface repairs

Manual application



Use



interior/
exterior

Application thickness



3 mm

Working time



Unlimited

Ready mixed

USE

DILUTION Ready mixed

APPLICATION

Conditions Do not apply at temperatures of below + 5°C or above + 35°C, or at a relative humidity above 80% H.R

Equipment Filling knife, blade

Operational mode Massage tube before application

Equipment cleaning With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

APPLICATION THICKNESS 3 mm

AVERAGE CONSUMPTION 1 L/m²/mm thickness

SUBSTRATES Concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, old painted substrates.
Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT Primer, filler, conventional paint, light-weight wall coverings



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



QUICK DRY FILLER

TECHNICAL DATA

COMPONANTS	Polymer base aqueous phase coat mix, mineral fillers, additives 80% of raw materials of natural origin (Calcium carbonate, water)
DENSITY	1,6 ± 0,1
pH	8 ± 1
COLOUR	White
WORKING TIME AT 20°C	Unlimited
WAITING TIME BEFORE OVERCOATING	Once completely dry
CLASSIFICATION	NF T 36-005 - Family IV, class 4b
NORM	NF EN 16566
V.O.C.	< 30 g/l (ready mixed)

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING 200 ml tube

STORAGE 12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. + 30°C) sun and moisture. Close well after use. Store in original packaging

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : January 2024

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

Beissier

Applying excellence

BEISSIER | Becket House - 1 Lambeth Palace Road - LONDON - SE1 7EU

Customer service : ☎ 020 7092 6696 | contact@beissier.eu