

WATERPROOF MASONRY FILLER



GENERAL INFORMATION

Description

Powder waterproof masonry filler

- Waterproofing, filling & finishing masonry substrate
- Repairing and shaping windows sills & mouldings

Intended use

- Interior/exterior

Manual application



Use



interior/
exterior

Application thickness



15 mm

Working time



30 min

Dilution



0,25L
1 kg

Advantages

- + Fills up to 15 mm in 1 application
- + Can be applied on damp substrates
- + Waterproof after 3 mm thickness
- + Repairs reinforced concrete, providing protection against carbonation process
- + Resistant to saltpeter and seawater
- + Flexible
- + Easy to mix
- + Easy to apply
- + Water vapour permeable
- + Grey

USE

DILUTION 25% - i.e. 0,25 liter of water per 1 kg of powder

PREPARATION Gradually pour the powder into the water, mixing until a homogeneous paste is obtained.

APPLICATION

Conditions Do not apply at temperatures of below + 5°C or above + 30°C, or at a relative humidity above 80% H.R

Equipment Filling knife, blade, smoothing trowel

Equipment cleaning With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

APPLICATION THICKNESS 15 mm

AVERAGE CONSUMPTION 1,2 kg/m²

SUBSTRATES Concrete, cellular concrete, cement, concrete block, brick, stone, mortars.
Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT Primer, filler, conventional paint, light-weight wall coverings.



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

WATERPROOF MASONRY FILLER



TECHNICAL DATA

COMPONANTS	Cement base coat mix, organic binder, fibres, mineral fillers, additives 30% of raw materials of natural origin (Calcium carbonate, sand)
pH	On mixing : 11,5 ± 1
COLOUR	Grey
WORKING TIME AT 20°C	Approximately 30 minutes
WAITING TIME BEFORE OVERCOATING	48 hours
CLASSIFICATION	NF T 36-005 - Family IV, class 4c
V.O.C.	< 0,5 g/l (ready mixed)

HEALTH AND SAFETY



Danger - contains cement
Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Avoid breathing dust. Wear suitable gloves and glasses. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING	1 kg box and 6 kg bag
STORAGE	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. + 30°C) sun and moisture. Close well after use. Store in original packaging

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : February 2024

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

Beissier

Applying excellence

BEISSIER | Becket House - 1 Lambeth Palace Road - LONDON - SE1 7EU

Customer service : ☎ 020 7092 6696 | contact@beissier.eu