



WOOD FILLER TUBE

GENERAL INFORMATION

Description

Ready mixed wood filler

Intended use

- Interior/exterior
- Filling holes & cracks on doors, window frames, skirting boards & floor boards

Manual application



Use



interior/
exterior

Application
thickness



5 mm

Working
time



Unlimited

Ready
mixed

Advantages

- + Flexible
- + Fibre glass reinforced
- + Quick drying
- + Easy to apply & sand
- + Suitable for use on most types of wood

USE

DILUTION Ready mixed

APPLICATION

Conditions Do not apply at temperatures of below + 5°C or above + 35°C, or at a relative humidity of above 80% H.R.

Equipment Filling knife, blade

Operational mode Massage tube before application. Work the filler into the repair and leave slightly proud for sanding. For deep repairs fill in two or more layers. Once dry sand and then stain, varnish or paint.

Equipment cleaning With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

RECOMMENDATIONS Exterior use : the filler must be over coated with a weather proof stain, varnish or paint. Do not apply on damp wood.

APPLICATION THICKNESS 5 mm

AVERAGE CONSUMPTION 1,4 kg/m²/mm thickness

SUBSTRATES Most types of wood, chipboard, plywood. **DO NOT APPLY ON DAMP WOOD.** Substrates must be clean, dry and free from dust, grease & wax. Metallic parts must be primed, according to the local standards.

OVERCOAT Primer, stain, varnish or paint.



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



WOOD FILLER TUBE

TECHNICAL DATA

COMPONANTS	Polymer base aqueous phase coat mix, mineral fillers, additives 70% of raw materials of natural origin (Calcium carbonate, water)
DENSITY	1,4 ± 0,1
pH	8 ± 1
COLOUR	White, natural, medium, dark
WORKING TIME AT 20°C	Unlimited
WAITING TIME BEFORE OVERCOATING	1 - 4 hours
CLASSIFICATION	NF T 36-005 - Family IV, class 4b
NORM	NF EN 16566
V.O.C.	< 30 g/l (ready mixed)

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Do not breathe dust. Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING

125 ml tube

STORAGE

12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. + 30°C) sun and moisture. Close well after use. Store in original packaging

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : January 2024

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

Beissier

Applying excellence

BEISSIER | Becket House - 1 Lambeth Palace Road - LONDON - SE1 7EU

Customer service : ☎ 020 7092 6696 | contact@beissier.eu