



WOOD REPAIR FILLER

GENERAL INFORMATION

Description

Powder wood filler

Intended use

- Interior/exterior

- Filling holes & cracks in all types of woodwork
- Reconstitute missing wood due to decay

Manual application



Use



interior/
exterior

Application thickness



Any
thickness

Working time



35 min

Dilution



0,50L

1 kg

Advantages

- + Easy to mix
- + Excellent adhesion to substrates
- + No thickness limitation
- + Very hard when dry
- + Ideal for repairing broken angles
- + Can be carved, drilled and painted
- + Can be tinted with a water based dye
- + Can be painted, stained, varnished and waxed
- + Easy to sand
- + Fine finish
- + White

USE

DILUTION 50% - i.e. 0,50 liter of water per 1 kg of powder
PREPARATION Gradually pour the powder into the water, mixing until a homogeneous paste is obtained.

APPLICATION

Conditions Do not apply at temperatures of below + 5°C or above + 35°C, or at a relative humidity above 80% H.R.

Equipment Filling knife, blade

Equipment cleaning With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

APPLICATION THICKNESS Any thickness

AVERAGE CONSUMPTION 1 kg of powder fills a volume of 1 liter

SUBSTRATES Most types of wood, including chipboard, plywood and exotic species.

Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT Varnishes, primers and conventional paint.



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).





WOOD REPAIR FILLER

TECHNICAL DATA

COMPONANTS	Polymer base aqueous phase coat mix, mineral fillers, additives 96% of raw materials of natural origin (Natural plaster, calcium carbonate, gypsum)
pH	7 ± 0,5
COLOUR	White
WORKING TIME AT 20°C	Approximately 35 minutes
WAITING TIME BEFORE OVERCOATING	Once completely dry
CLASSIFICATION	NF T 36-005 - Family IV, class 4c
NORM	NF EN 16566
V.O.C.	< 0,1 g/l (ready mixed)

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Do not breathe dust. Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING	1 kg box
STORAGE	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. + 30°C) sun and moisture. Close well after use. Store in original packaging

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : January 2024

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

Beissier

Applying excellence

BEISSIER | Becket House - 1 Lambeth Palace Road - LONDON - SE1 7EU

Customer service : ☎ 020 7092 6696 | contact@beissier.eu